



125-CBRN1 Canister

THIS CANISTER IS APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS		RESPIRATOR COMPONENTS																												Cautions and Limitations ^{2/3}				
TC-	Protection ¹	Canister	Alternated Full Facepiece	Alternate Breathing Valve	Pressurization Hose	Alternate Breathing Hose	Hose Cover	Exhalation Valve	Fan Unit	Alternate Batteries	Alternate Battery Charger	Gang Battery Conditioner	Alternate Harness	Foam Insert	Accessory Hood	Hose Latch Retainer	Alternate Speaker Unit	Waist Belt Extension	Data Cable	SEWIN Software	Power Supply	Power Supply 12V Vehicle	Power Cord 110V US	Prefilter	Prefilter Holder	Visor Cover (Disposable)	Accessory Eye Wear Insert	Accessory Belt Attachment						
		125-CBRN1	RF3-FP-C	FP-C	DV3-C	H20-P	H20	HC-TF	EVS	SE40	B1	DB1	BC1	BC3	GBCO	WB1	BP2	SEA-FI	H-TYVF	HLR	ST1-A-20	ST2-F	WB-EX	DC-A-2	SEWIN	PS1	PSV-12	PC-USA	221	PFH-T	VC	FSF-T	HSE	
14G-0290	CBRN PAPR CAP 1	X	X		X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	AFHIJLMNORSYZ,BB,CC,GG,QQ,UU,VV
14G-0299	CBRN CAP 1	X		X														X				X						X	X	X	X	X	AJLMORTVWXYZ,CC,HH,QQ,UU	
14G-0300	CBRN PAPR CAP 1	X	X		X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	AFHIJLMNORSYZ,BB,CC,GG,QQ,UU,VV

1. PROTECTION

CBRN PAPR Cap 1 - Capacity meets minimum 15 minutes test time
CBRN Cap 1 - Capacity meets minimum 15 minutes test time
CBRN - Chemical, Biological, Radiological and Nuclear

2. CAUTIONS AND LIMITATIONS

- A Not for use in atmospheres containing less than 19.5 percent oxygen.
- F Do not use powered air-purifying respirators if airflow is less than four cfm (115 lpm) for tight fitting facepieces or six cfm (170 lpm) for hoods and/or helmets.
- H Follow established cartridge and canister change schedules or observe ESLI to ensure that cartridges and canisters are replaced before breakthrough occurs.
- I Contains electrical parts that may cause an ignition in flammable or explosive atmospheres.
- J Failure to properly use and maintain this product could result in injury or death.
- L Follow the manufacturer's User's Instructions for changing cartridges, canisters and/or filters.
- M All approved respirators shall be selected, fitted, used and maintained in accordance with MSHA, OSHA and other applicable regulations.
- N Never substitute, modify, add or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- O Refer to User's Instructions and/or maintenance manuals for information on use and maintenance of these respirators.
- S Special or critical User's Instructions and/or specific use limitations apply. Refer to User's Instructions before donning.
- BB Not for use for entry into atmospheres immediately dangerous to life and health.
- CC For entry, do not exceed maximum use concentrations established by regulatory standards.

3. CBRN CAUTIONS AND LIMITATIONS

- R Some CBRN agents may not present immediate effects from exposure, but can result in delayed impairment, illness, or death.
- T Direct contact with CBRN agents requires proper handling of the respirator after each use and between multiple entries during the same use. Decontamination and disposal procedures must be followed. If contaminated with liquid chemical warfare agents, dispose of the respirator after decontamination.
- V Not for use in atmospheres immediately dangerous to life and health or where hazards have not been fully characterized.
- W Use replacement parts in the configuration as specified by the applicable regulations and guidance.
- X Consult manufacturer's User's Instructions for information on the use, storage, and maintenance of these respirators at various temperatures.
- Y This respirator provides respiratory protection against inhalation of radiological and nuclear dust particles. Procedures for monitoring radiation exposure and full radiation protection must be followed.
- Z If during use, an unexpected hazard is encountered such as a secondary CBRN device, pockets of entrapped hazard or any unforeseen hazard, immediately leave the area for clean air.
- GG Direct contact with CBRN agents requires proper handling of the respirator after use. Correct disposal procedures must be followed.
- HH When used at defined occupational exposure limits, the rated service time cannot be exceeded. Follow established canister change schedules or observe End of Service Life Indicators to ensure that canisters are replaced before breakthrough occurs.
- QQ Use in conjunction with personal protective ensembles that provide appropriate levels of protection against dermal hazard. Failure to do so may result in personal injury even when the respirator is properly fitted, used, and maintained.
- UU The respirator should not be used beyond eight (8) hours after initial exposure to chemical warfare agents to avoid possibility of agent permeation. If liquid exposure is encountered, the respirator should not be used for more than two (2) hours.
- V V PAPRS with TC-23C approvals may NOT be used for escape from IDLH atmospheres.