

DATA SHEET

Sundström air hood SR 83 for welding



Updated: 06 Mar 2007

Description:	Compressed air hood with welding shield
Product name:	SR 83
Hood material:	Wear-resistant leather
Visor:	Polycarbonate
Welding cassette:	Designed for welding visor and protective visor of standard 60 x 110 mm size (2.36" x 4.33").
Helmet:	The hood comes with a removable safety helmet.
Head harness:	The interior head harness is adjustable from the outside.
Regulator:	Belt mounted regulator. 150—280 litres/minute.
Warning whistle:	Alarms when flow dips below 150 l/min.
Recommended compressor power:	4—7 bar
Breathing hose:	Kink and tangle proof.
Temperature range:	–10°C to +60°C (14°F to 140°F).
Noise level:	<66 dB(A)
Weight:	1,280 g (2.8 lbs)
Accessories:	Clear plastic tear-off visor protectors.
Also included:	Flow meter for monitoring of supplied air flow.
Parts:	<ol style="list-style-type: none"> 1. Helmet 2. Welding cassette 3. Welding visor 4. Protective visor 5. Hood 6. Breathing hose 7. Adjustment strap 8. Belt 9. Regulator 10. Warning whistle 11. Supplied air hose 12. Head harness 13. Flow meter

