

## DATA SHEET

### Sundström SR540 supplied air shield



Updated: 16 May 2008

<b>Description:</b>	Protective shield for use with SR500 and compressed air supply.
<b>Product name:</b>	Sundström SR540 protective supplied air shield
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Protects the respiratory organs, the face, and the crown of the head</li> <li>• Hinged visor unit</li> <li>• Scratch-resistant and chemical-resistant polycarbonate visor</li> <li>• Air supply keeps visor mist-free</li> <li>• Adjustable head harness</li> <li>• Replaceable breathing air hose</li> <li>• Exhalation valve</li> <li>• Optional PETG visor, peel-offs and head cover</li> </ul>
<b>Air flow rate:</b>	<ul style="list-style-type: none"> <li>• 175 l/min (normal operation)</li> <li>• 225 l/min (boost fan operation)</li> </ul>
<b>Temperature range:</b>	<ul style="list-style-type: none"> <li>• Operation: -10°C to +55°C (14°F to +131°F) at &lt;90% relative humidity</li> <li>• Storage: -20°C to +40°C (-4°F to +104°F) at &lt;90% relative humidity</li> </ul>
<b>Low flow warning:</b>	<175 l/min
<b>Weight with hose:</b>	700 g (24.7 oz)