

---

# Data Sheet: Sundström SR63

---



## Supplied air hood

<b>Description</b>	Soft protective hood for connection through supplied regulator to a fixed supplied-air system
<b>Features</b>	<ul style="list-style-type: none"><li>— Fits over the entire head</li><li>— Often a good solution for bearded users</li><li>— Durable PVC-supported nylon material</li><li>— Replaceable, crush-proof, scratch-proof polycarbonate visor</li><li>— Tear-off visor film available</li><li>— Use with supplied regulator with extra outlet for compressed air tools such as spray guns</li></ul>
<b>Material</b>	PVC-supported nylon — resistant to chemicals, non-spark material
<b>Working pressure</b>	4 to 7 bar
<b>Air flow</b>	150 to 240 l/min
<b>Temperature range</b>	<ul style="list-style-type: none"><li>— Operation: <math>-10^{\circ}\text{C}</math> to <math>+55^{\circ}\text{C}</math> at <math>&lt;90\%</math> RH</li><li>— Storage: <math>-20^{\circ}\text{C}</math> to <math>+40^{\circ}\text{C}</math> at <math>&lt;90\%</math> RH</li></ul>
<b>Weight</b>	770 g approx. without regulator
<b>Low flow warning</b>	$<150$ l/min
<b>Noise</b>	$<70$ dB(A) inside hood