Sundström

Manufactured in Sweden since 1926

Supplied-Air System

SR99-1 Compressed Air Filter

PVC hose*

*Available in various lengths
*Anti-static black hose also available

SR63 Compressed Air Hood System

SR200A Full-Face Respirator Supplied-Air System

SR507 Supplied-Air Attachment

SR307 Supplied-Air Attachment

SR100 Half-Face Respirator

SR200 Full-Face Respirator

Compatible Head-Top Options

SR900
Half-Face Mask

SR520
Soft Face Shield

SR530
Soft Face & Neck Hood

SR570
Face Shield

SR575
Safety Helmet

SR601
Microchem®
2800 Soft Hood

SR602
Microchem®
4000 Soft Hood

The S.E.A. Group
sea.com.au

Safety Equipment Australia Pty Ltd

SEA.Enquiries@sea.com.au

1800 655 129 | +61 2 9910 7500

Certified System ISO 9001 Quality

Sundström

Manufactured in Sweden since 1926

Supplied-Air System

Airline (Supplied-Air) systems deliver a continuous supply of clean breathing air when contaminant concentrations exceed exposure limits, making them ideal for toxic chemical handling, abrasive blasting, spray painting, confined space entry, and other high-risk environments.

SR507 Airline System

- SR507 Compressed-Air Attachment is designed for use with the Sundström SR520 Soft Face Shield, SR530 Hood, SR570 Face Shield, SR575 and SR580 Safety Helmet, and SR601 and SR602 hoods.
- Belt mounted, manufactured from non-sparking materials, resistant to chemicals, with an integrated warning whistle that activates if airflow drops below safe operating levels.
- Airflow: 175 to 260 L/min
- Working pressure: 5 to 7 bar
- Low flow warning level: < 150 L/min

SR307 Airline System

- The SR307 Compressed-Air Attachment is designed for use with the Sundström SR63 Compressed-Air hood, SR100 and SR900 Half-Face Respirators, and SR200 Full-Face Respirator.
- Belt mounted, manufactured from non-sparking materials, resistant to chemicals, with an integrated warning whistle that activates if airflow drops below safe operating levels.
- Airflow: 150 to 320 L/min
- Working pressure: 4 to 7 bar
- Low flow warning level: < 150 L/min

SR99-1 Compressed Air Filter

- Produces breathing quality air at 900 L/min
- Suitable for use with pneumatic tools and instruments
- Floor or wall-mounted
- Inlet pressure: 6 to 10 bar
- Pre-separator with automatic drainage, separates coarser particles, water and oil

SR292 Replacement Filter

- Filter cartridge replacement designed for the SR99-1 compressed air filter
- Type A protects against oils, organic gases and vapours, such as solvents, with boiling points > +65 °C
- Type P3 protects against all types of particulate pollutants, e.g. dust, mist and smoke
- Typical service life: approximately 6 months (subject to operating conditions and air quality)

The S.E.A. Group
sea.com.au

Safety Equipment Australia Pty Ltd
SEA.Enquiries@sea.com.au
1800 655 129 | +61 2 9910 7500

Certified System
ISO 9001
Quality